


**TYPE 1 CROSS RECESS  
PAN HEAD MACHINE SCREW  
w/ SPLIT LOCKWASHER  
SEMS**

88MXXXPPS
APRIL, 2014
REV 00
PAGE 1 of 1

Nominal Screw Length	Tolerance On Length
Up To & Including 3mm"	±0.20
Over 3mm To 10mm, Inclusive	±0.30
Over 10mm to 16mm, Inclusive	±0.40
Over 16mm to 50mm, Inclusive	±0.50
Over 50mm	±1.00



Nominal Screw Size	Major Diameter		"Dk"		"K"		Driver Size	Recess Penetration Gaging Depth		Washer Diameter		Washer Thk.
	Max.	Min.	Max.	Min.	Max.	Min.		Max.	Min.	Max.	Min.	Min.
M3 x 0.5	2.980	2.874	5.60	5.30	2.40	2.20	1	1.80	1.40	5.73	5.49	1.02
M4 x 0.7	3.978	3.838	8.00	7.60	3.10	2.80	2	2.40	1.90	7.00	6.74	1.19

Standard: ASME B18.13.1M Material: Screw: 300 Series Stainless Steel (Tensile Stress: 700 MPa Min.) Washer: 300 Series Stainless Steel Rc30-40 Finish: Passivate	<b>Common Uses:</b> Used in applications where loosening is a concern. These washers are designed to maintain tension on the screw from relaxation of the joint to reduce loosening of the joint.
--	--